Noise Tester NF-562

NEW

Application

NF-562 is a professional noise tester with portable size, stable functionality, the device can direct, accurate and fast test the decibel level in any environment; Mainly used in construction field, entertainment venue, living community etc to monitor the noise level of the environment.

Function Illustration

1 ON/OFF Button:

Long press for 2s to turn on the device Short press to turn off the device.

2 Fast/Slow Button:

Switch between 125ms fast mode and 1s slow mode.

③ MAX/MIN Button:

Switch the measuring level between max value and min value, 1st short press to display the max value, 2nd short press to display Min value, and 3rd short press to exit the MAX/MIN measuring mode. When in MAX/MIN mode the device will always display the max/min value during the measuring.

4 HOLD/Backlight Button:

Short press to store current data, short press again to exit store function; long press for 2s to turn on backlight and long press again to turn off the backlight.

5 Low Power Alert And Auto-off

Power Alert Mode:

The power sign will alert when the battery power is lower than the amount needed for working.

Auto-Off Mode

The device will auto-off when the power is too low to operate or without any operation within 5 minutes.

Technical Parameter

| | NF-562 Technical In | dex |
|-----------------------|-----------------------------|----------|
| Display | FSTN LCD Screen | |
| Buttons | 4 Function Buttons | |
| Sensor | Capacity Microphone | |
| Noise Testing | Testing Range | 30-130dB |
| | Testing Accuracy | ±1.5dB |
| | Resolution | 0.1dB |
| Testing Speed | FAST | 125ms |
| | SLOW | 1S |
| Over range alert | $\sqrt{}$ | |
| MAX/MIN testing | $\sqrt{}$ | |
| Auto-off | 5 Minutes Without Operation | |
| Data Store/Backlight | \checkmark | |
| LCD backlight control | \checkmark | |
| Low power alert | \checkmark | |
| Battery | 3*1.5V/AAA | |
| Dimension | 50 X 30 X160mm | |